

C205WSHR 8.5kW 16A 3 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



	Overall dimensions (W x D x H)	mm	633 x 750 x 2253* (inc. feet)
	Packaging dimensions (W x D x H)	mm	760 x 840 x 1600 (720 x 760 x 310)
	Gross weight	kg	105 (19)
	Net weight	kg	89 (23)
	Cubic Volume	m ³	0.98 (0.18)
	Rack size (W x D x H)	mm	500 x 500 x 155
	Door opening	mm	470
	Max useable height	mm	440
	Rack guide rails		St/St frame with composite guides
	Body construction		single skin
	Tank construction		moulded
	Tank volume	L	20
	Tank heating element	kW	3.0 (3x1 with Thermofuse)
	Surface scrap trays		composite (2mm mesh)
	Wash arms (with cleaning port)		parallel (quick release)
	Wash pump type		dual flow
	Wash pump power	kW	0.47
	Pre-set wash temperatures	°C	60 (Pr1, Pr2, Pr3 adjustable)
	Boiler type		open
	Boiler volume	L	7.0
	Breaktank		yes
	Boiler heating element	kW	5.0 (1+2+2 with Thermofuse)
	Rinse booster pump		yes
	Rinse booster pump power	kW	0.2
	Pre-set rinse temperatures	°C	82 (Pr1, Pr2, Pr3 adjustable)
	Rinse arms		parallel (quick release)
	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes (built into sump)
	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Water softener		yes
	Water consumption per cycle	L	1.4-4.0
	Inlet water pressure	bar	1.0-4.0
	Inlet water temperature	°C	10-50 (cold fill recommended)
	Total programs	programs	10
	Total power	kW	8.5
	Fuse	A	16
	Electric connection (as supplied)	V-PH-HZ	400V 3+N 50Hz
	Configurable to		not convertible
	Heat recovery fan	kW	0.76
	Heat recovery air flow	m ³ /h	405
	Residual heat emission SENSITIVE	kW	0.8
	Residual heat emission LATENT	kW	0.6



	Display	Time (sec)
P button	Pr1	75
	Pr2	95
	Pr3	115
	dr	variable
	CLEn	variable
SP button	Pr6	160
	bot1	variable
	bot2	variable
	GLS2	100
	LonG	600

Supplied with (Standard configuration)

Open glass rack	1
Pegged dish rack	1
Single cutlery rack	1
Electric cable (H07RN-F 3G6)	1
Drain hose (Ø Int 19mm, Ext 24mm)	1
Fill hose (3/4" BSP)	1
Feet	4




*Minimum height (+60mm with adjustable feet) †Minimum height with hood open (+60mm with adjustable feet)
Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.

T: 03451 308 070
E: sales@maidaid-halcyon.co.uk
Issue: 3.1 31/07/26

C205WSHR 8.5kW 16A 3 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



A		Ø 32 mm
B		G 3/4"
C		Power supply

All dimensions in mm.

All services must be within 1 metre.

*Minimum height (+60mm with adjustable feet) †Minimum height with hood open (+60mm with adjustable feet)
Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.

T: 03451 308 070
E: sales@maidaid-halcyon.co.uk
Issue: 3.1 31/07/26