

C35D

2.75kW 13A 1 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



	Overall dimensions (W x D x H)	mm	401 x 490 x 605 (inc. feet)
	Packaging dimensions (W x D x H)	mm	470 x 590 x 750
	Gross weight	kg	31
	Net weight	kg	27
	Cubic Volume	m ³	0.25
	Rack size (W x D x H)	mm	350 x 350 x 120
	Door opening	mm	260
	Max useable height	mm	240
	Rack guide rails		embossed
	Body construction		stratified double skin
	Tank construction		welded - stamped base
	Tank volume	L	7
	Tank heating element	kW	1.4 (without Thermofuse)
	Surface scrap trays		composite (2mm mesh)
	Wash arms (with cleaning port)		parallel (quick release)
	Wash pump type		single flow
	Wash pump power	kW	0.15
	Pre-set wash temperatures	°C	60-65 (GLS1, GLS2, GLS3 adjustable)
	Boiler type		pressurised
	Boiler volume	L	2.6
	Breaktank		no
	Boiler heating element	kW	2.6 (without Thermofuse)
	Rinse booster pump		no
	Rinse booster pump power	kW	n/a
	Pre-set rinse temperatures	°C	65-70 (GLS1, GLS2, GLS3 adjustable)
	Rinse arms		parallel (quick release)
	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes
	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Water softener		no
	Water consumption per cycle	L	2.0-2.5
	Inlet water pressure	bar	2.0-2.5
	Inlet water temperature	°C	10-50
	Total programs	programs	6
	Total power	kW	2.75
	Fuse	A	13
	Electric connection (as supplied)	V-PH-HZ	230-240V 1N 50Hz
	Configurable to		not convertible



	Display	Time (sec)
P button	GLS1	80
	GLS2	90
	GLS3	100
	dr	variable
	CLEn	variable
SP button	CuP1	105

Supplied with
(Standard configuration)

Open glass rack	2
Single cutlery rack	
Electric cable (3x1.5mm moulded plug)	1
Drain hose (Ø Int 19mm, Ext 24mm)	1
Fill hose (3/4" BSP)	1
Feet	4

Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.


T: 03451 308 070
E: sales@maidaid-halcyon.co.uk
Issue: 3.1 31/07/26

C35D

2.75kW 13A 1 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



Feet adjustable +10mm.

All services must be within 1 metre.

All dimensions in mm.