

RANGE GUIDE

C Range Dishwashers



midea

C51D

Undercounter

midea

built for the demands of modern hospitality



9 **versatile** wash programs



EN17735 **hygiene certified**



Up to **25% less water** per cycle



LED digital display panel & design features



0.2 kWh **low energy** consumption

performance data

Independent certified testing confirms C Range's outstanding performance across all key metrics

Wash Effectiveness



100%

Xc

from 100% - full cleaning power

Energy Consumption



0.2

kWh (Ec)

per cycle - ultra low energy use

Water Consumption



1.5

ltr (Wc)

ultra low water per cycle

Cycle Time



297

secs (Tc)

fast turnaround per wash cycle

Power Use



0.19

kW (Pu)

low power draw during operation

what's new

Old Model		New Model
USER BENEFITS		
LED soft touch 4 button control	→	LED digital display – 4 button control
Old handle – poorer quality & ergonomics	→	New stainless steel handle: improved robustness & ergonomics
7 wash programs	→	9 wash programs
Flat rack rails	→	Embossed rail racks
		Easy-remove wash arms & tank system
OPERATIONAL IMPROVEMENTS		
Avg water consumption 2.0 ltr	→	Avg water consumption 1.5 ltr
		Low energy consumption from 0.2 kWh
Partial double skin	→	Double stratified skin
Optional drain pump	→	Integrated drain pump
Hygiene standard EN17735	→	Hygiene standard EN17735
		Integral tank strainers
		Evolved electronic components
		Improved wash performance & heat retention
Dual tank filter	→	Triple tank filter



C RANGE DISHWASHERS



The C Range delivers high performance with simple, intuitive operation. Versatile and reliable, it's ideal for operations that demand quality and efficiency while minimising energy and water consumption.

Key Attributes

- Capacitive touch LED display
- Drain pump fitted on all models
- Low water usage (from 1.5L)
- Improved energy efficiency (25% less*)
- Stratified double skin for improved heat retention
- Up to 9 programs
- Triple filter system
- Surface scrap tray filters supplied as standard
- Proven performance, tested to EN 17735 & EN 63136:2019
- 18 plate rack capacity (500x500 basket)
- 2 year warranty

Intelligent Functions & Advanced Technologies		C51D	C55 WSD	C61D	C65 WSD	C62D
SUSTAINABILITY	 Patented dual flow wash pump - reduces power consumption whilst retaining wash efficiency	■	■	■	■	■
	 Selectable thermostop ensures optimum rinse temperatures	■	■	■	■	■
	 Partial Drain System provides cleaner wash water for better wash results	■	■	■	■	■
	 Triple filtration system that reduces pump wear and tear	■	■	■	■	■
	 Highly efficient rinse system that delivers perfect wash results with minimal water consumption	■	■	■	■	■
	 Selectable energy saving mode	■	■	■	■	■
	 Patented washarm geometry optimises water distribution whilst maintaining cleaning performance	■	■	■	■	■
OPERATION	 Quick release wash arms with removable caps for easier cleaning	■	■	■	■	■
	 Easy tank access and a mirrored finish makes maintenance and cleaning easier	■	■	■	■	■
	 Soft start pump that protects delicate washware & prolongs pump life	■	■	■	■	■
	 Alarms menu with hi-level information retrieval	■	■	■	■	■
VERSATILITY	 Accurate detergent & rinse aid peristaltic dosing pumps as standard	■	■	■	■	■
	 Multiple power configurations available	■	■	■	■	■
	 Automatic continuous internal water softener		■		■	
	 Breaktank	■	■	■	■	■
	 Bottle wash system for dedicated bottle washing	■	■			



C Range Dishwashers

Four button capacitive touch LED display ensures clear visibility of temperatures and system messages. The twin colour coded indicator bars provide status updates and operational self diagnostics, while the robust, scratch-resistant synthetic glass front panel combines durability with sleek, modern design.

Technical Data		C51D	C55WSD	C61D	C65WSD	C62D
Dimensions (W x D x H)	mm	575 x 605 x 820*	575 x 605 x 820*	575 x 700 x 850*	575 x 700 x 850*	575 x 700 x 1225*
Rack size	mm	500 x 500	500 x 500	500 x 600	500 x 600	500 x 600
Maximum useable height	mm	330	330	380	380	380
Door opening	mm	365	365	405	405	405
Theoretical productivity	Racks/h	48	48	45	45	45
Effective productivity**	Racks/h	34	34	33	33	33
Wash tank element	kW	2.0	2.0	2.0	2.0	2.0
Boiler element	kW	6.0†	6.0†	6.0†	6.0†	6.0†
Wash pump	kW	0.47	0.47	0.7	0.7	0.7
Tank capacity	L	20	20	23	23	23
Racks - open / pegged		1/1	1/1	1/1	1/1	1/1

* Minimum height (+10mm with adjustable feet). **Allowing 30 seconds for reloading. Cycle times may vary depending on local conditions/services.

† Max rating - dependent on model power configuration. See Tech Sheet for more info.

Packaging Specs		C51D	C55WSD	C61D	C65WSD	C62D
Gross weight	Kg	67	70	68	72	88
Cubic volume	m³	0.45	0.45	0.52	0.52	0.65
Dim. (W x D x H)	mm	670 x 690 x 980	670 x 690 x 980	670 x 780 x 1000	670 x 780 x 1000	780 x 670 x 1250

Power Supply		C51D	C55WSD	C61D	C65WSD	C62D
Electric connection	V-Ph-Hz	230-240V 1N 50 HZ				
Fuse	A	13				
Total Power	kW	2.5		2.7		
Electric connection	V-Ph-Hz	230-240V 1N 50 HZ				
Fuse	A	20				
Total Power	kW	4.5		4.7		
Electric connection	V-Ph-Hz	230-240V 1N 50 HZ				
Fuse	A	30				
Total Power	kW	6.5		6.7		
Electric connection	V-Ph-Hz	400V 3+N 50Hz				
Fuse	A	16				
Total Power	kW	7.5		7.7		

Water Connection		C51D	C55WSD	C61D	C65WSD	C62D
Inlet water pressure	Bar	1.0 - 4.0	1.0 - 4.0	1.0 - 4.0	1.0 - 4.0	1.0 - 4.0
Water inlet temp	°C	10 - 50	10 - 50	10 - 50	10 - 50	10 - 50
Water connection	BSP	3/4"	3/4"	3/4"	3/4"	3/4"

Cycle Information		C51D	C55WSD	C61D	C65WSD	C62D
Wash cycles		3	3	3	3	3
Special cycles		4	4	4	4	4
Wash cycle times	Sec	75 - 600	75 - 600	80 - 600	80 - 600	80 - 600
Cleaning cycles		2	2	2	2	2
Water consumption per cycle	L	1.5 - 2.0	1.5 - 2.0	1.8 - 2.6	1.8 - 2.6	1.8 - 2.6
Wash temperature	°C	55 - 60	55 - 60	55 - 60	55 - 60	55 - 60
Rinse temperature	°C	70 - 82	70 - 82	70 - 82	70 - 82	70 - 82

*Independent results from EN63136 testing vs comparable specification machines across the market

*Independent results from EN63136 testing vs comparable specification machines across the market.

Maidaid reserve the right to alter specs & dimensions without prior notification,

all dimensions will be +/- 3mm.

Issue 2.0 ; 27/3/26

The Engine Shed
Top Station Road, Brackley NN13 7UG

t: 0345 130 8070

e: sales@maidaid-halcyon.co.uk

www.maidaid.co.uk