

D50

7.5kW 16A 3 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



	Overall dimensions (W x D x H)	mm	600 x 615 x 715 (722-737 inc. feet)
	Packaging dimensions (W x D x H)	mm	670 x 690 x 880
	Gross weight	kg	58
	Net weight	kg	50
	Cubic Volume	m ³	0.45
	Rack size (W x D x H)	mm	500 x 500 x 155
	Door opening	mm	300
	Max useable height	mm	270
	Rack guide rails		embossed
	Body construction		fully double skin
	Hood / Door Construction		fully double skin
	Tank construction		moulded
	Tank volume	L	15
	Tank heating element	kW	2.0 (without Thermofuse)
	Surface scrap trays		composite (2mm mesh)
	Wash arms (with cleaning port)		parallel (quick release)
	Wash pump type		dual flow
	Wash pump power	kW	0.47
	Pre-set wash temperatures	°C	60 (GLS1, GLS2, GLS3 adjustable)
	Boiler type		pressurized
	Boiler volume	L	6.0
	Breaktank		no
	Boiler heating element	kW	5.0 (2+2+1 without Thermofuse)
	Rinse booster pump		no
	Rinse booster pump power	kW	n/a
	Pre-set rinse temperatures	°C	65 (GLS1, GLS2, GLS3 adjustable)
	Rinse arms		parallel (quick release)
	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes (built into sump)
	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Water softener		no
	Water consumption per cycle	L	1.4-2.5
	Inlet water pressure	bar	2.0-4.0
	Inlet water temperature	°C	10-50
	Total programs	programs	9
	Total power	kW	7.5
	Fuse	A	16
	Electric connection (as supplied)	V-PH-HZ	400V 3N 50Hz
	Configurable to		not convertible



	Display	Time (sec)
P button	GLS1	85
	GLS2	100
	GLS3	110
	dr	variable
	CLEn	variable
SP button	Pr6	160
	CuP1	115
	LonG	600
	d1	variable

Supplied with

(Standard configuration)

Open glass rack	2
Single cutlery rack	1
Electric cable (H07RN-F 5G2.5)	1
Drain hose (Ø Int 19mm, Ext 24mm)	1
Fill hose (3/4" BSP)	1
Feet (7-22mm)	4

Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.


T: 03451 308 070
E: sales@maidaid-halcyon.co.uk
Issue: 3.1 31/07/26

D50

7.5kW 16A 3 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



All services must be within 1 metre.

All dimensions in mm