

# EVO 212COP 6.7kW 32A 1 Phase



**Buttress Group Ltd.**  
Top Station Road, Brackley,  
Northants NN13 7UG, UK



|  |                                   |                |                                                 |
|--|-----------------------------------|----------------|-------------------------------------------------|
|  | Overall dimensions (W x D x H)    | mm             | <b>633 x 750 x 1560* (2060)*</b><br>(inc. feet) |
|  | Packaging dimensions (W x D x H)  | mm             | <b>870 x 760 x 1600</b>                         |
|  | Gross weight                      | kg             | <b>105</b>                                      |
|  | Net weight                        | kg             | <b>89</b>                                       |
|  | Cubic Volume                      | m <sup>3</sup> | <b>1.00</b>                                     |
|  | Rack size (W x D x H)             | mm             | <b>500 x 500 x 155</b>                          |
|  | Door opening                      | mm             | <b>470</b>                                      |
|  | Max useable height                | mm             | <b>440</b>                                      |
|  | Rack guide rails                  |                | <b>St/St frame with composite guides</b>        |
|  | Body construction                 |                | <b>double skin</b>                              |
|  | Hood / Door Construction          |                | <b>double skin fully insulated</b>              |
|  | Tank construction                 |                | <b>moulded</b>                                  |
|  | Tank volume                       | L              | <b>20</b>                                       |
|  | Tank heating element              | kW             | <b>3.0 (3x1 with Thermofuse)</b>                |
|  | Surface scrap trays               |                | <b>Stainless Steel (1.5mm mesh)</b>             |
|  | Wash arms (with cleaning port)    |                | <b>parallel (quick release)</b>                 |
|  | Wash pump type                    |                | <b>dual flow</b>                                |
|  | Wash pump power                   | kW             | <b>0.7</b>                                      |
|  | Pre-set wash temperatures         | °C             | <b>60 (P1,P2,P3 adjustable)</b>                 |
|  | Boiler type                       |                | <b>Open</b>                                     |
|  | Boiler volume                     | L              | <b>7.0</b>                                      |
|  | Breaktank                         |                | <b>yes</b>                                      |
|  | Boiler heating element            | kW             | <b>6.0 (2+2+2 with Thermofuse)</b>              |
|  | Rinse booster pump                |                | <b>Yes</b>                                      |
|  | Rinse booster pump power          | kW             | <b>0.2</b>                                      |
|  | Pre-set rinse temperatures        | °C             | <b>82 (P1,P2,P3 adjustable)</b>                 |
|  | Rinse arms                        |                | <b>parallel (quick release)</b>                 |
|  | Drain system                      |                | <b>partial drain</b>                            |
|  | Drain filter                      |                | <b>triple filter</b>                            |
|  | Drain pump                        |                | <b>yes (built into sump)</b>                    |
|  | Steam condenser heat recovery     |                | <b>no</b>                                       |
|  | Rinse aid dispenser               | peristaltic    | <b>yes</b>                                      |
|  | Detergent dispenser               | peristaltic    | <b>yes</b>                                      |
|  | Water softener                    |                | <b>no</b>                                       |
|  | Water consumption per cycle       | L              | <b>1.4-4.0</b>                                  |
|  | Inlet water pressure              | bar            | <b>1.0-4.0</b>                                  |
|  | Inlet water temperature           | °C             | <b>10-50</b>                                    |
|  | Total programs                    | programs       | <b>24</b>                                       |
|  | Total power                       | kW             | <b>6.7</b>                                      |
|  | Fuse                              | A              | <b>32</b>                                       |
|  | Electric connection (as supplied) | V-PH-HZ        | <b>230-240V 1N 50Hz</b>                         |
|  | Configurable to                   | W-A            | <b>4.7kW 20A</b>                                |
|  | Configurable to                   | W-A            | <b>6.7kW 16A 3-phase</b>                        |
|  | Cut-Off-Power system              |                | <b>yes</b>                                      |

## Available Programs

### General Cluster:

P1 (75s – 82/60°C),  
P2 (95s – 82/60°C),  
P3 (115s – 82/60°C),  
G2, Drain

## Other Clusters including 24

### Programs:

Fine  
Canteen  
Bar / Bistro  
Deli / Shop  
Pastry Shop  
Health Care  
Fast Food  
Festivals

## Supplied with

(Standard configuration)

|                                   |   |
|-----------------------------------|---|
| Pegged dish rack                  | 1 |
| Open Glass rack                   | 1 |
| Single cutlery rack               | 1 |
| Electric cable (H07RN-F 3G6)      | 1 |
| Drain hose (Ø Int 25mm, Ext 31mm) | 1 |
| Fill hose (¾" BSP)                | 1 |
| Feet (165-225mm)                  | 4 |

\*Minimum height (+60mm with adjustable feet) †Minimum height with hood open (+60mm with adjustable feet)  
Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.




T: 03451 308 070  
E: sales@maidaid-halcyon.co.uk  
Issue: 3.1 03/08/26

# EVO 212COP

6.7kW 32A  
1 Phase



**Buttress Group Ltd.**  
Top Station Road, Brackley,  
Northants NN13 7UG, UK



|   |  |              |
|---|--|--------------|
| A |  | Ø 32 mm      |
| B |  | G 3/4"       |
| C |  | Power supply |

All dimensions in mm

\*Minimum height (+60mm with adjustable feet) †Minimum height with hood open (+60mm with adjustable feet)  
Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.

T: 03451 308 070  
E: sales@maidaid-halcyon.co.uk  
Issue: 3.1 03/08/26