

EVO40WS

2.8kW 13A
1 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



	Overall dimensions (W x D x H)	mm	466 x 556 x 700 (705-715 inc. feet)
	Packaging dimensions (W x D x H)	mm	560 x 660 x 870
	Gross weight	kg	50
	Net weight	kg	57
	Cubic Volume	m ³	0.32
	Rack size (W x D x H)	mm	400 x 400
	Door opening	mm	320
	Max useable height	mm	290
	Rack guide rails		embossed
	Body construction		fully double skin
	Hood / Door Construction		fully insulated
	Tank construction		moulded
	Tank volume	L	8
	Tank heating element	kW	1.4 (without Thermofuse)
	Surface scrap trays		stainless steel (1.5mm mesh)
	Wash arms (with cleaning port)		parallel (quick release)
	Wash pump type		dual flow
	Wash pump power	kW	0.2
	Pre-set wash temperatures	°C	60-65 (G1,G2,G3 fully adjustable)
	Boiler type		Open
	Boiler volume	L	2.6
	Breaktank		yes
	Boiler heating element	kW	2.6 (without Thermofuse)
	Rinse booster pump		Yes
	Rinse booster pump power	kW	0.15
	Pre-set rinse temperatures	°C	65-70 (G1,G2,G3 fully adjustable)
	Rinse arms		parallel (quick release)
	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes
	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Water softener		yes (continuous)
	Water consumption per cycle	L	2-2.5
	Inlet water pressure	bar	1.0-4.0
	Inlet water temperature	°C	10-50
	Total programs	programs	8
	Total power	kW	2.8
	Fuse	A	13
	Electric connection (as supplied)	V-PH-HZ	230-240V 1N 50Hz
	Configurable to		not convertible



Available Programs

Water Master Cluster:

G1 (75s – 65/65°C),
G2 (90s – 60/70°C),
G3 (100s – 60/65°C),
P3,
Drain

8 Programs including:

G1
G2
G3
C1
Drain
Self-clean
Refresh

Supplied with

(Standard configuration)

Open glass rack	2
Single cutlery rack	1
Electric cable (H07RN-F 3G4)	1
Drain hose (Ø Int 19mm, Ext 24mm)	1
Fill hose (3/4" BSP)	1
Feet (5-15mm)	4

Maidaid reserve the right to alter specification & dimensions without prior notification, all dimensions will be +/- 3mm. Machines fitted to cold water supply may not be capable of running repeated short cycles. The cycle time will be automatically extended to allow for recovery of correct operating temperatures.


T: 03451 308 070
E: sales@maidaid-halcyon.co.uk
Issue: 2.0 09/03/26

EVO40WS

2.8kW 13A
1 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



All services must be within 1 metre.

All dimensions in mm